

WPA Techno



- R410a Refrigerant Circuit
- Aluminum Microchannel Condenser
- Shell and Tube Evaporator
- Electronic Expansion Valve
- Axial Fans
- Pump and Tank on board (option)
- Electrical Level Indicator
- General Alarm Signals



WPA Standard

CODICE - CODE - ARTIKELNUMMER - CÒDIGO	M.U.	WPA060		WPA070		WPA080		WPA090		WPA100		WPA110		
Capacità di raffreddamento - Cooling capacity - Kühlleistung - Potencia frigorífica	W15L32	kW	210,5	460,3	237,7	460,3	298,3	460,3	314,2	460,3	343	460,3	416,3	
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W15L32	kW	51,8	60	63,2	60	71,6	60	82	60	91,7	60	99,7	
SEPR			5,36		5,36		5,02		5,72		5,68		5,88	
Capacità di raffreddamento - Cooling capacity - Kühlleistung - Potencia frigorífica	W7L35	kW	165,5	460,3	187,5	460,3	222,6	460,3	245,2	460,3	266,5	460,3	318,6	
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W7L35	kW	53,2	60	64,4	60	73,7	60	83	60	91,6	60	100,4	
Gas refrigerante - Refrigerant gas - Kältemittel - Gas refrigerante			R410A		R410A		R410A		R410A		R410A		R410A	
Carica gas refrigerante - Charge refrigerant gas - Kältemittelfüllung - Carga de refrigerante		kg	18		17,5		17		18		15,5		22,5	
Circuiti frigo/Compressori - Cooling circuits/Compressors - Schaltungen - Kühlschrank/Kompressoren - Circuitos/Compresores		N°	2 / 4		2 / 4		2 / 4		2 / 4		2 / 4		2 / 4	
Tensione nominale - Rated voltage - Nennspannung - Tensión nominal		V-	400,3	460,3	400,3	460,3	400,3	460,3	400,3	460,3	400,3	460,3	400,3	460,3
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal		Hz	50	60	50	60	50	60	50	60	50	60	50	60
Altezza x Larghezza x Profondità - Height x Width x Depth - Höhe x Breite x Tiefe - Altura x Anchura x Profundidad		mm	2410x3100x2206		2410x3100x2206		2410x3100x2206		2410x3100x2206		2410x3100x2206		2410x4400x2206	
Peso a vuoto - Shipping weight - Gewicht - Peso		kg	2293		2323		2395		2420		2440		3119	

CODICE - CODE - ARTIKELNUMMER - CÒDIGO	M.U.	WPA120		WPA140		WPA160		WPA180		WPA200		
Capacità di raffreddamento - Cooling capacity - Kühlleistung - Potencia frigorífica	W15L32	kW	460,3	460,3	499,9	460,3	564,9	460,3	657,3	460,3	727,4	
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W15L32	kW	114,1	60	129,5	60	132,1	60	174,1	60	200,6	
SEPR			5,62		5,87		5,84		5,79		6,18	
Capacità di raffreddamento - Cooling capacity - Kühlleistung - Potencia frigorífica	W7L35	kW	353,1	460,3	385,1	460,3	432	460,3	504	460,3	559,3	
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W7L35	kW	114,2	60	127,5	60	131,9	60	173,6	60	199,8	
Gas refrigerante - Refrigerant gas - Kältemittel - Gas refrigerante			R410A		R410A		R410A		R410A		R410A	
Carica gas refrigerante - Charge refrigerant gas - Kältemittelfüllung - Carga de refrigerante		kg	25		24,5		69		80,5		89	
Circuiti frigo/Compressori - Cooling circuits/Compressors - Schaltungen - Kühlschrank/Kompressoren - Circuitos/Compresores		N°	2 / 4		2 / 4		2 / 4		2 / 6		2 / 6	
Tensione nominale - Rated voltage - Nennspannung - Tensión nominal		V-	400,3	460,3	400,3	460,3	400,3	460,3	400,3	460,3	400,3	460,3
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal		Hz	50	60	50	60	50	60	50	60	50	60
Altezza x Larghezza x Profondità - Height x Width x Depth - Höhe x Breite x Tiefe - Altura x Anchura x Profundidad		mm	2410x4400x2206		2410x4400x2206		2410x5770x2206		2410x5770x2206		2410x5770x2206	
Peso a vuoto - Shipping weight - Gewicht - Peso		kg	3173		3219		4158		4559		4561	

Your trusted temperature & humidity control partners
Sales Service Rental