

## NR-475 Hire Chiller

## **Product Overview**

Robust design - Specifically designed for demanding process cooling applications

Ecodesign compliant - all models fully comply with ErP2021 - SEPR HT (EU) 2016/2281 - SEPR MT (EU) 2015/1095

Wide operating range - operates in ambient temperatures from +45°C down to -10°C with cooling fluid supply temperatures between +20°C and -10°C

Eco-friendly - built around the latest high-efficiency scroll compressors utilising low GWP R454B refrigerant

Shell & tube evaporator - a robust solution providing greater dependability compared to more traditional designs

Coated condenser coils - aluminium microchannel construction results in a smaller refrigerant charge - while epoxy coating offers protection in potentially aggressive environments

Dual independent refrigeration circuits - additional resilience provides greater peace of mind

Isolation valves & strainers - fitted to fluid connections

## Performance Data

N	lominal Cooling Capacity (1)	470 kW
N	lominal Power Consumption (1)	126 kW
	ER (1)	
	perating Limits linimum/Maximum Cooling Fluid Flow Rate	44/108 m³/hr
E	lectrical Data	
P	lower Supply	400/3/50 V/ph/Hz
	ower Connections - Hard Wired	
	laximum Running Current	
	laximum Starting Current	
	P Rating	
R	cooling Circuit defrigerant / Compressor Typelumber of Compressors / Circuits / Fans	
Н	lydraulic Circuit	
N	lominal Cooling Fluid Flow Rate (1)	80.8 m <sup>3</sup> /hr
N	lominal Evaporator Pressure Drop (1)	67 kPa
C	onnections	4" Flanged
	hysical Data	
	ength (2)	
	/idth (2)	
	eight (2)	
	perating Weight (2)	
S	ound Pressure Level (2)	62 dB(A)



(1) Performance data based on operating conditions of +7°C cooling fluid outlet temperature / +12°C cooling fluid inlet temperature / +30°C ambient temperature

(2) Sound pressure at 10m average value obtained in a free field on a reflecting plane at a distance of 10m from the unit, non-binding value calculated from the sound power level

## Still have a question?

Get in touch with one of our expert team today.



01422 371711



sales@newsome.ltd.uk



www.newsome.ltd.uk







The level of performance provided by each machine depends on the conditions at which it is operating.

The two factors determining performance are ambient air temperature and the required cooling fluid outlet temperature.

The above graphs illustrate the cooling capacity and nominal running current – at three different operating ambient temperatures – based on differing cooling fluid outlet temperatures





