

## NR-375 Hire Chiller

## **Product Overview**

Robust design - Specifically designed for demanding process cooling applications

Ecodesign compliant - all models fully comply with ErP2021 - SEPR HT (EU) 2016/2281 - SEPR MT (EU) 2015/1095

**Wide operating range** - operates in ambient temperatures from +45°C down to -10°C with cooling fluid supply temperatures between +20°C and -10°C

Eco-friendly - built around the latest high-efficiency scroll compressors utilising low GWP R454B refrigerant

Shell & tube evaporator - a robust solution providing greater dependability compared to more traditional designs

Coated condenser coils - aluminium microchannel construction results in a smaller refrigerant charge - while epoxy coating offers protection in potentially aggressive environments

Dual independent refrigeration circuits - additional resilience provides greater peace of mind

Isolation valves & strainers - fitted to fluid connections

## Performance Data

Nominal Cooling Capacity (1)	370 kW
Nominal Power Consumption (1)	98.3 kW
EER (1)	
Operating Limits	
Minimum/Maximum Cooling Fluid Flow Rate	39/93 m <sup>3</sup> /hr
Electrical Data	
	/ 00 /7 /F0 W/ I- /II-
Power Supply	
Power Connections - Hard Wired	
Maximum Running Current	
Maximum Starting Current	522 A
IP Rating	IP54
Cooling Circuit	
Refrigerant / Compressor Type	D/.E/.D/Coroll
Number of Compressors / Circuits / Fans	4/ 2/ 0
Hydraulic Circuit	
Nominal Cooling Fluid Flow Rate (1)	63 6 m <sup>3</sup> /hr
Nominal Evaporator Pressure Drop (1)	
Connections	
CONNECTIONS	4 Flallyeu
Physical Data	
Length (2)	4,335 mm
Width (2)	
Height (2)	
Operating Weight (2)	
Sound Pressure Level (2)	
South Liessaig Peaciff)	39 uD(A)

(1) Performance data based on operating conditions of +7°C cooling fluid outlet temperature / +12°C cooling fluid inlet temperature / +30°C ambient temperature

O) newsome

(2) Sound pressure at 10m average value obtained in a free field on a reflecting plane at a distance of 10m from the unit, non-binding value calculated from the sound power level

## Still have a question?

Get in touch with one of our expert team today.



01422 371711



sales@newsome.ltd.uk



www.newsome.ltd.uk







The level of performance provided by each machine depends on the conditions at which it is operating.

The two factors determining performance are ambient air temperature and the required cooling fluid outlet temperature.

The above graphs illustrate the cooling capacity and nominal running current – at three different operating ambient temperatures – based on differing cooling fluid outlet temperatures.





