

# NR-PAC P9 Portable Cooler

NR-PAC P9

## Product Overview

**Eco-friendly** – portable monblock units comprising the latest technology which utilises low GWP R454C refrigerant

**High efficiency** – backward curved fan impellers coupled with variable speed EC motors

**Digital thermostatic control** – possible for the user to set a desired set point using the integrated controller

**Twin discharge ducts** – allowing for cooling of two separate areas simultaneously

**Exhaust duct** – can be ducted up to 10m away allowing units to be sited away from warm exhaust point



## Performance Data

Nominal Cooling Capacity (1) .....8.3 kW  
 Nominal Air FlowRate.....1080 m<sup>3</sup>/hr  
 Typical Cooled Area.....220 m<sup>3</sup>

### Operating Limits

Minimum/Maximum Cooling Fluid Flow Rate ..... 15/35 °C

### Electrical Data

Power Supply .....230/1/50 V/ph/Hz  
 Power Connections .....13A 3 pin plug  
 IP Rating ..... IP2X

### Cooling Circuit

Refrigerant ..... R454C  
 Exhaust Duct (Max. length 10m) .....200 mmØ  
 Discharge Ducts (Max. length 1.25m).....2 x 150 mmØ

### Physical Data

Length (2) ..... 774 mm  
 Width (2) .....526 mm  
 Height (2) .....1,192 mm  
 Operating Weight (2) .....95 kg

## Still have a question?

Get in touch with one of our expert team today.

- ☎ 01422 371711
- ✉ sales@newsome.ltd.uk
- 🌐 www.newsome.ltd.uk

