

NR-PAC S7 Portable Cooler

NR-PAC S7

Product Overview

Eco-friendly – portable split units comprising the latest technology which utilises low GWP R454C refrigerant

High efficiency – backward curved fan impellers coupled with variable speed EC motors

Digital thermostatic control – possible for the user to set a desired set point using the integrated controller

Separate exhaust unit – no additional ductwork required

Umbilical extension hoses – exhaust unit can be sited up to 15 m away from main cooling unit via additional extension hoses



Performance Data

Nominal Cooling Capacity (1) 7.4 kW
 Nominal Air FlowRate 1,100 m³/hr
 Typical Cooled Area 220 m³

Operating Limits

Minimum/Maximum Cooling Fluid Flow Rate 15/35 °C

Electrical Data

Power Supply 230/1/50 V/ph/Hz
 Power Connection 13A 3 pin plug
 IP Rating (Cooling unit/exhaust unit) IP2X/IP24

Cooling Circuit

Refrigerant R454C
 Maximum umbilical length 35 m
 Maximum height of exhaust unit (when sited above cooling unit) 5m

Physical Data

Length - Cooling Unit 805 mm
 Width - Cooling Unit 382 mm
 Height - Cooling Unit 1,308 mm
 Operating Weight - Cooling Unit 90 kg
 Operating Weight - Exhaust Unit 22 kg

Still have a question?

Get in touch with one of our expert team today.

- ☎ 01422 371711
- ✉ sales@newsome.ltd.uk
- 🌐 www.newsome.ltd.uk

