

# NR-IDF100 Indirect Diesel Fired Heater

NR-IDF100

## Product Overview

**Versatile** - robust mobile indirect diesel fired heater suitable for a wide range of different applications

**Dual voltage capability** - can operate on either 110 / 230 volt power supplies via selector switch

**High efficiency** - integral heat exchanger achieves 92% efficiency

**Robust Design** - complete with durable body panels, large wheels & forklift slots

**Digital Thermostat** - manages the fan, the burner & provides overheat protection



## Performance Data

Nominal Heating Capacity ..... 110 kW  
 Nominal Air Flow Rate..... 8,000 m<sup>3</sup> /hr  
 Nominal Fuel Consumption ..... 10.9 l/hr  
 Maximum Ventilation Back Pressure..... 300 Pa

### Electrical Data

Power Supply - Dual Voltage ..... 110-230/1/50 V/ph/Hz  
 Power Connections ..... 32 A  
 Power Connection - 230V Supply ..... 16 A

### Heating Circuit

Spigot Connections ..... 500 mm Ø  
 Maximum Discharge Duct Length ..... 18 m  
 Flue Connection Size..... 200 mm  
 Flue Height..... 1 m

### Physical Data

Length ..... 2,230 mm  
 Width ..... 780 mm  
 Height ..... 1,340 mm  
 Operating Weight ..... 350 kg

## Still have a question?

Get in touch with one of our expert team today.

-  01422 371711
-  sales@newsome.ltd.uk
-  www.newsome.ltd.uk

