

NR-IDF70 Indirect Diesel Fired Heater

NR-IDF70

Product Overview

Versatile – robust mobile indirect diesel fired heater suitable for a wide range of different applications

Dual voltage capability – can operate on either 110 / 230 volt power supplies via selector switch

High efficiency – integral heat exchanger achieves 91% efficiency
Robust design – complete with durable body panels, bumper, large wheels & forklift slots

Large integral fuel tank – 120 litre tank with level switch provides up to 16 hours operation – it is also possible to connect a separate external fuel tank if desired



Performance Data

Nominal Heating Capacity70 kW
Nominal Air Flow Rate.....3,800 m³ /hr
Nominal Fuel Consumption 7.0 l/hr
Maximum Ventilation Back Pressure.....200 Pa

Electrical Data

Power Supply - Dual Voltage 110-230/1/50 V/ph/Hz
Power Connections16A

Heating Circuit

Spigot Connections400 mm Ø
Maximum Discharge Duct Length..... 18 m
Flue Connection Size.....180 mm
Flue Height.....1 m
Integral Fuel Tank Volume..... 120 litres

Physical Data

Length1,920 mm
Width690 mm
Height1,170 mm
Operating Weight 165 kg

Still have a question?

Get in touch with one of our expert team today.

☎ 01422 371711
✉ sales@newsome.ltd.uk
🌐 www.newsome.ltd.uk

