

# NR-H2000DF Dual Fuel Boiler

NR-H2000DF

## Product Overview

**Versatile** – condensing boilers suitable for use with either diesel or gas burners  
– for use within a wide range of different applications

**Weatherproof** – installed within a steel frame suitable for external siting

**Fully packaged** – complete with all necessary safety valves/switches along with flexible connections to ease installation

**Wide range of ancillaries available** – fuel tanks, fuel lines, calorifiers, hoses & cables can all be supplied to provide a complete solution



## Performance Data

Nominal Heating Capacity.....2,000 kW  
Nominal Fuel Consumption – Diesel ..... 215 l/hr  
Nominal Fuel Consumption – Gas .....240 m<sup>3</sup>/hr

### Operating Limits

Minimum/Maximum Heating Fluid Supply Temperature ..... 50/90 °C  
Maximum Working Pressure ..... 5.0 bar

### Electrical Data

Power Supply .....400/3/50 V/ph/Hz  
Power Connection ..... 63 A 5 Pin Plug

### Hydraulic Circuit

Nominal Heating Fluid Flow Rate ..... 115 m<sup>3</sup>/hr  
Connections .....150 mm  
Expansion Tank Volume ..... 1,000 litres

### Physical Data

Length .....6,096 mm  
Width .....2,439 mm  
Height .....2,621 mm  
Operating Weight.....10,500 kg

## Still have a question?

Get in touch with one of our expert team today.

☎ 01422 371711  
✉ sales@newsome.ltd.uk  
🌐 www.newsome.ltd.uk

