

NR-H300DF Dual Fuel Boiler

NR-H300DF

Product Overview

Versatile – condensing boiler suitable for use with either diesel or gas burner – for use within a wide range of different applications

Weatherproof – installed within a steel frame suitable for external siting

Fully packaged – complete with all necessary safety valves/switches along with flexible connections to ease installation

Suitable for single phase supply – large heating capacity is achieved from a relatively small electrical load

Wide range of ancillaries available – fuel tanks, fuel lines, calorifiers, hoses & cables can all be supplied to provide a complete solution



Performance Data

Nominal Heating Capacity..... 300 kW
 Nominal Fuel Consumption – Diesel 32 l/hr
 Nominal Fuel Consumption – Gas 34 m³/hr

Operating Limits

Minimum/Maximum Heating Fluid Supply Temperature 50/90 °C
 Maximum Working Pressure 6.0 bar

Electrical Data

Power Supply 230/1/50 V/ph/Hz
 Power Connection 16 A 3 Pin Plug

Hydraulic Circuit

Nominal Heating Fluid Flow Rate 18 m³/hr
 Connections 50 mm
 Expansion Tank Volume 200 litres

Physical Data

Length 3,300 mm
 Width 1,200 mm
 Height 2,300 mm
 Operating Weight 2,300 kg

Still have a question?

Get in touch with one of our expert team today.

☎ 01422 371711
 ✉ sales@newsome.ltd.uk
 🌐 www.newsome.ltd.uk

