

# NR-IDF200 Indirect Diesel Fired Heater

NR-IDF200

## Product Overview

**Versatile** - robust mobile indirect diesel fired heater suitable for a wide range of different applications

**High efficiency** - integral heat exchanger achieves 92% efficiency

**Robust Design** - complete with durable stainless steel body panels, box girders & forklift slots

**Digital Thermostat** - manages the fan, the burner & provides overheat protection



## Performance Data

Nominal Heating Capacity .....	200 kW
Nominal Air Flow Rate.....	12,000 m <sup>3</sup> /hr
Nominal Fuel Consumption .....	20.0 l/hr
Maximum Ventilation Back Pressure.....	600 Pa

### Electrical Data

Power Supply - Dual Voltage .....	400/3/50 V/ph/Hz
Power Connections .....	32 A

### Heating Circuit

Spigot Connections .....	600 mm Ø
Maximum Discharge Duct Length.....	42 m
Flue Connection Size.....	200 mm
Flue Height.....	1 m

### Physical Data

Length .....	2,400 mm
Width .....	800 mm
Height .....	1,350 mm
Operating Weight .....	545 kg

## Still have a question?

Get in touch with one of our expert team today.

-  01422 371711
-  sales@newsome.ltd.uk
-  www.newsome.ltd.uk

