

NR-PAC P6 Portable Cooler

NR-PAC P6

Product Overview

Eco-friendly – portable monblock units comprising the latest technology which utilises low GWP R454C refrigerant

High efficiency – backward curved fan impellers coupled with variable speed EC motors

Digital thermostatic control – possible for the user to set a desired set point using the integrated controller

Twin discharge ducts – allowing for cooling of two separate areas simultaneously

Exhaust duct – can be ducted up to 10m away allowing units to be sited away from warm exhaust point



Performance Data

Nominal Cooling Capacity (1)6.5 kW
 Nominal Air FlowRate..... 1,200 m³/hr
 Typical Cooled Area.....150 m³

Operating Limits

Minimum/Maximum Cooling Fluid Flow Rate2l/35 °C

Electrical Data

Power Supply230/1/50 V/ph/Hz
 Power Connections13A 3 pin plug
 IP Rating IP2X

Cooling Circuit

Refrigerant R454C
 Exhaust Duct (Max. length 10m)150 mmØ
 Discharge Ducts (Max. length 1.25m).....2 x 150 mmØ

Physical Data

Length (2) 774 mm
 Width (2)526 mm
 Height (2)1,086 mm
 Operating Weight (2)92 kg

Still have a question?

Get in touch with one of our expert team today.

- ☎ 01422 371711
- ✉ sales@newsome.ltd.uk
- 🌐 www.newsome.ltd.uk

